

VISCOBOND LTD

Unit 210 Holly Road, Western Ind.Estate

Naas Road, Dublin 12, D12 RW8E

Contact details:

Phone: 00353-1-6932019

Email: stephen@viscobondtapes.com

Web: www.viscobondtapes.com

6002 White DOUBLE-SIDED PE FOAM TAPE

6002 is a high-performance double-sided tape, with a white polyethylene foam carrier and solvent acrylic adhesive. The product has a moisture stable green filmic release liner.

APPLICATIONS

- Aluminium spacer profile bonding to glass
- External vehicle mirror assembly bonding
- Bonding of PVC decorative trims
- Bonding plastic profiles (cable management)

| | |
|---|--|
| ADHESIVE TYPE | SOLVENT ACRYLIC |
| DENSITY | 83KG |
| CARRIER | PE FOAM |
| TAPE COLOUR | WHITE |
| TAPE THICKNESS | 1mm, 2mm, 3mm ± (100µm) |
| RELEASE LINER THICKNESS | 130µm |
| TOTAL THICKNESS | 1.1mm, 2.1mm , 3.1mm ±100um |
| RELEASE LINER | GREEN FILMIC |
| STATIC SHEARING (HOLDING POWER) (GB/T4851-2014) (24MMX24MM) | 1000g, 5.76cm ² 1440min+ |
| INITIAL TACK ROLLING BALL GB/T4852-2002 (14#STEEL BALL) | <50MM |
| SOLVENT RESISTANCE | GOOD |
| TEMPERATURE RESISTANCE | 80°C |
| SHELF LIFE | 12 MONTHS |
| STORAGE CONDITIONS | 21°C (70°) & 50% RELATIVE HUMIDITY |



Application-Guidelines: Surfaces must be clean, dry, free from grease and dirt. Please note manufacturers safety instructions should be followed and customers are recommended to ensure compatibility of the solvent and their substrate. Ideal bonding substrates are those which are: clean, dry, flat, smooth, dust free and non-porous. Low temperatures may increase the risk of condensation, reducing the tack of the product. Life expectancy will vary with temperature and humidity. Product may be applied by hand direct from a roll applying even pressure. The information supplied is accurate to the best of our knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss and does not form part of any contract with a customer whatsoever and however arising.